

GRINDING & SANDING

Pneumatic Grinder

MYTON

Heavy-duty grinders for tough applications

- Side exhaust with noise reduction system
- Great power/weight ratio


Model MYG-25

- For Grinding Wheel 58 mm
- Compact and lightweight type



Model MYG-40

- For Grinding Wheel 100 mm
- Powerful type



Model MAGW-40

- Lever switch type
- Depressed center wheel 100 mm



Model MAGW-40 Non-CE

- Ring switch type
- Depressed center wheel 100 mm



Specifications

Model	MYG-25	MYG-40	MAGW-40 Lever Type	MAGW-40 Ring Type
Air Pressure	MPa (kgf/cm ²) 0.6 (6)			
Air Consumption	m ³ /min 0.68 (No-load) 0.82 (Load)			
Free Speed	min ⁻¹ (rpm) 19000 13000			
Depressed Center Grinding Wheel	mm 58 100			
Inlet Size	Rc 1/4 Rc 3/8			
Mass (Weight)	kg 0.6 1.5			
Accessories Included	<ul style="list-style-type: none"> • 5 mm Hex. Socket Screw Key • 19 mm Single Ended Spanner • Grinding Wheel GS #80 x 58 • Bushing R 1/4 x NPT 1/4 	<ul style="list-style-type: none"> • 5 mm Hex. Socket Screw Key • 6 mm Hex. Socket Screw Key • Bushing R 3/8 x NPT 3/8 	<ul style="list-style-type: none"> • 6 mm Hex. Socket Screw Key • 17 mm Single Ended Spanner • Bushing R 3/8 x NPT 3/8 	

Model MAG-50

- For Grinding wheel 125 mm
- Heavy grinding type



Model MYG-50

- Lever switch type
- For Grinding wheel 125 mm
- Heavy grinding type



Model MYG-70

- Lever switch type
- For Grinding wheel 180 mm
- Heavy grinding type



Model MYG-70 Non-CE

- Ring switch type
- For Grinding wheel 180 mm
- Heavy grinding type



Specifications

Model	MAG-50	MYG-50	MYG-70 Lever Type	MYG-70 Ring Type
Air Pressure	MPa (kgf/cm ²) 0.6 (6)			
Air Consumption	m ³ /min 0.77 (No-load) 0.83 (Load) 0.75 (No-load) 0.70 (No-load) 0.95 (Load)			
Free Speed	min ⁻¹ (rpm) 12000 11000 7600			
Depressed Center Grinding Wheel	mm 125 180			
Inlet Size	Rc 3/8			
Mass (Weight)	kg 2.2 2.5 (with handle) 2.4 (with handle)			
Accessories Included	<ul style="list-style-type: none"> • Air Hose Sub Ass'y • Exhaust Hose Ass'y • Side Handle (anti-vibration type) • 4 mm Hex Socket Screw Key • Pin Face Wrench • Bushing R 3/8 x NPT 3/8 	<ul style="list-style-type: none"> • Handle (anti-vibration type) • 4 mm Hex. Socket Screw Key • 6 mm Hex. Socket Screw Key • Pin Face Wrench • Bushing R 3/8 x NPT 3/8 	<ul style="list-style-type: none"> • Handle • 6 mm Hex. Socket Screw Key • 10 mm Hex. Socket Screw Key • Bushing R 3/8 x NPT 3/8 	