

MODEL **KW - 19HP**

*1/2" Sq. Dr. Impact Wrench
The Most Powerful*



APPLICATIONS :

- Tyre setting work of light car & passenger vehicle
- Assembly / disassembly work for engine or underbody
- Setting work for U-bolt.

SPECIFICATIONS : (Performance figures are at 0.62 MPa(Pe) / 90 P.S.I. air pressure.)

Drive Size	1/2 in	
Capacity of Bolt Size	18 mm	11/16 in
Free Speed	6,000 r.p.m.	
Impact Per Min.	1,200 i.p.m.	
Recommended Torque	100-450 Nm	75-335 ft.lbs
Maximum Torque	500 Nm	370 ft.lbs
Weight (w/o socket)	2.4 kg	5.2 lbs
Length (w/o socket)	178 mm	7 in
Air Consumption	0.40 m ³ /min	14.3 c.f.m.
Hose Size	6.3 mm	1/4 in
Air Pressure	0.62 MPa	90 P.S.I.



KUKEN CO., LTD.

3-6-15 Nonoue, Habikino-shi, Osaka 583-0871, Japan
Tel : +81-72-953-3346 Fax : +81-72-953-0605
Web : www.kuken.co.jp/english E-mail : export1@kuken.co.jp



CAT. No. 250314-19