

MODEL **KW-20P**

3/4" Sq. Dr. Impact Wrench



APPLICATIONS :

- Tyre & U-bolt setting work for small trucks.
- Maintenance work for engine of heavy truck.
- Bridge construction.
- Ship-building equipments.
- Construction machinery.

SPECIFICATIONS : (Performance figures are at 0.62 MPa(Pe) / 90 P.S.I. air pressure.)

Drive Size	19.0 mm	3/4 in
Capacity of Bolt Size	20 mm	1-3/4 in
Free Speed	4,500 r.p.m.	
Impact Per Min.	1,080 i.p.m.	
Recommended Torque	150-650 Nm	110-480 ft.lbs
Maximum Torque	870 Nm	630 ft.lbs
Weight (w/o socket)	KW-20P	4.2 kg ... 9.2 lbs
	KW-20P-2	4.3 kg ... 9.5 lbs
	KW-20P-6	4.6 kg ... 10.0 lbs
Length (w/o socket)	KW-20P	241 mm ... 9-1/2 in
	KW-20P-2	279 mm ... 10-3/4 in
	KW-20P-6	384 mm ... 14-7/8 in
Air Consumption	0.47 m ³ /min	16.7 c.f.m.
Hose Size	12.7 mm	1/2 in
Air Pressure	0.62 MPa	90 P.S.I.



KUKEN CO., LTD.

3-6-15 Nonoue, Habikino-shi, Osaka 583-0871, Japan

Tel : +81-72-953-3346 Fax : +81-72-953-0605

Web : www.kuken.co.jp/english E-mail : export1@kuken.co.jp



CAT. No. 250314-20P