



KDA15EVF

KODIAK BLAST CHILLER
15 TRAYS 600X400 - GN 1/1
DIGITAL DISPLAY



FUNCTIONAL CHARACTERISTICS

Display	Digital
Supply	ELECTRIC
Number of evaporator motors	2
Evaporator Motor speeds	1
Number of condenser motors	1
Condenser Motor speeds	1
Min chamber temperature (°C)	-35 °C
Core probe	PTC
Chamber material	Fingerprint free co-laminated steel
Frame material	Fingerprint free co-laminated steel
Opening door	Right handle
Door gasket	Magnetic removable
Door frame	Heated inspectable
Insulation	CFC-HFC free HD Poliurethane 60mm

STANDARDS

Certification	CE
---------------	----

TRAYS

Trays rack	Wire PA-BIV 15/70
Max tray load	4 kg

DIMENSIONS

Blast chiller size with handle WxDxH (mm)	790 x 760 x 1950
Chamber gross volume (L)	376 L
Chamber usefull volume (L)	342 L
Unit weight (Kg)	161 kg

PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	910 x 910 x 2090
Unit weight with packaging (Kg)	183 kg



ELECTRICAL DATA

Compressor 400V 3N~ 50Hz

Power	3500 W
Frequency	50 Hz
Power supply	400V 3N~
Amperage	6,74 A

REFRIGERATION CIRCUIT

Cooling capacity**	4767 W
Cooling capacity per cycle (+90°C > +3°C)	40 kg
Freezing capacity per cycle (+90°C > -18°C)	25 kg
Refrigerant	R452a
Refrigerant load	1,4 kg
Evaporator	Anti-corrosion coating
Climate class	5 (43°C)
Defrost	Evaporator fan
CO2 equivalent	3,92 Tons

FUNCTIONS

Blast chilling cycles	Soft / hard
Deep Freezing	Soft / hard
Temperature regulation	Core probe / Time
Storage	+3°C/-18° automatic
Fish sanitification	Not Available
Ice cream	Not Available
Recipes	Not Available
Thowing	Not Available

CONNECTIVITY

USB	-
Bluetooth	-
Wi-Fi	-
Cloud	-

**Evap-10°, Cond. 45



ACCESSORIES

Stacking kit (SQUERO)	Not available
Stacking kit (SAN GIORGIO SAN MARCO)	Not available
Heated core probe	Optional
Pvoting wheel kit h80	R80
Pvoting wheel kit h100	R100
Ice cream kit	Not available

